

Year	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

APPLICANTS: JOHN R. JACOBSON, RUSSELL P. HAZARD

Allison Johnson
Printed Name of Person Mailing Application

COATING APPARATUS

Background of the Invention

The invention is directed to coating articles.

5 A roll of pressure sensitive adhesive tape is often prepared by applying a pressure sensitive adhesive composition to a backing and then winding the backing on a cylindrical core to form the roll of tape. The edge face of the roll of tape often includes exposed pressure sensitive adhesive, which renders the edge face tacky. In addition, when the tape is wound upon a cylindrical core to form a roll, uneven winding may occur which may
10 cause variations in the edge face surface.

Multiple rolls of pressure sensitive adhesive tape are often packaged in a stack. When rolls of pressure sensitive adhesive tape are stacked on top of one another they tend to block, i.e., stick together. Blocking tends to increase in frequency and degree over time and at elevated temperatures, e.g., above room temperature. The edge face of a roll of tape
15 may also stick to its packaging, which can make removal of the roll of tape from the packaging difficult. Electrical tape, for example, which is often sold in plastic containers, tends to stick to the plastic walls of the container. The tacky nature of the edge face also tends to pick up dust, dirt and other particulate debris from the environment.

A number of methods have been developed to protect the edge face of a roll of
20 adhesive tape or detackify the exposed adhesive on the edge face. One common method involves placing a sheet of paper in contact with the edge face, e.g., between two rolls of tape. Another method involves coating the edge face of a roll of tape with very small glass beads. The glass beads tend to fall off the roll, which can cause contamination or damage to manufacturing processes and machinery. Other methods include applying a
25 detackifying agent to the edge of a strip of tape using a sponge or a cloth prior to winding the strip of tape upon a cylindrical core to form a roll.

Summary

In one aspect, the invention features an apparatus for coating an article, the apparatus comprising an applicator, a conveyor for sequentially transporting a plurality of
30 articles to the applicator and a metering bar positioned against the applicator to meter a predetermined amount of coating composition to the applicator for transfer to an article transported to the applicator by the conveyor. In one embodiment, the applicator includes

a roller having a durometer of no greater than about 55 Shore A. In another embodiment, the coating apparatus is capable of applying a substantially uniform layer of coating composition on a plurality of articles having different dimensions.

5 In some embodiments, the end of the metering bar positioned against the roller has a radius of at least about 2.5 mm. In other embodiments, the end of the metering bar positioned against the roller has a radius of at least about 4.0 mm. In another embodiment, the metering bar exerts a force of at least about 35 g/cm width against the applicator. In some embodiments, the metering bar exerts a force of from about 45 g/cm width to about 900 g/cm width against the applicator.

10 In one embodiment, the conveyor is positioned relative to the applicator such that the applicator is capable of coating the edge face of a roll of tape disposed between the conveyor and the applicator. In one embodiment, the applicator is a roller. In other embodiments, the applicator is an endless belt.

15 In other embodiments, the apparatus further includes a second applicator and a second metering bar positioned against the second applicator to meter a predetermined amount of coating composition to the second applicator, the second applicator being positioned to receive an article from the conveyor. In one embodiment, the first applicator is a roller and the second applicator is a roller. In other embodiments, the first applicator includes an endless belt. In some embodiments, the second applicator includes an endless
20 belt.

In another embodiment, the apparatus is capable of substantially simultaneously transferring a coating composition from the first applicator to a first side of an article, and transferring a coating composition from the second applicator to a second side of the article opposite the first side of the article. In some embodiments, the article is a roll of
25 tape and the apparatus is capable of substantially simultaneously transferring a coating composition from the first applicator to a first edge face of a roll of tape and transferring a coating composition from the second applicator to a second edge face of the roll of tape opposite the first edge face of the roll of tape.

In one embodiment, the first applicator and the second applicator are positioned to
30 maintain an article between the first applicator and the second applicator.

In another aspect, the invention features a system for manufacturing coated articles, the system including a first station comprising a coating apparatus that includes an applicator, a conveyor capable of sequentially transporting a plurality of articles to the applicator, and a metering bar positioned against the applicator to meter a predetermined amount of coating composition to the applicator for transfer to an article transported to the applicator by the conveyor, and a second station for solidifying the coating composition disposed on the article.

In some embodiments, the applicator includes a roller. In other embodiments, the applicator includes an endless belt.

In another embodiment, the conveyor is capable of transporting a coated article to the second station.

In other embodiments, the system further includes a second conveyor capable of transporting a coated article from the first station to the second station. In one embodiment, the system further includes a second conveyor comprising a first endless belt and a second endless belt, the second conveyor being positioned to transport a coated article to the second station. In some embodiments, the system further includes a second applicator positioned to receive an article from the conveyor, and a second metering bar positioned against the second applicator to meter a predetermined amount of coating composition to the second applicator. In another embodiment, the system further includes a second applicator positioned opposite the first applicator, and a second metering bar positioned against the second applicator to meter a predetermined amount of coating composition to the second applicator. In one embodiment, the system further includes a second conveyor positioned to transport a coated article to the second station. In another embodiment, the system further includes a second conveyor comprising a first endless belt and a second endless belt, the second conveyor being positioned to transport a coated article to the second station. In one embodiment, the second conveyor is capable of transporting a coated article between the first endless belt and the second endless belt.

In some embodiments, the second station includes a source of radiation. In one embodiment, the source of radiation is capable of generating radiation selected from the group consisting of ultraviolet radiation and electron beam radiation. In other

embodiments, the solidifying includes curing. In yet other embodiments, the solidifying includes drying.

In another aspect, the invention features a method of coating an article using a coating apparatus comprising an applicator, a conveyor for transporting an article the applicator, and a metering bar positioned against the applicator to meter a predetermined amount of coating composition to the applicator, the method including applying a liquid coating composition to the applicator and transferring the coating composition from the applicator to the article. In some embodiments, the coating composition has a viscosity of at least about 15 cps. In other embodiments, the coating composition has a viscosity of at least about 19 cps. In one embodiment, the method further includes curing the coated composition. In another embodiment, the method further includes drying the coated composition

In some aspects, the invention features a method of coating the edge face of a roll of tape using a coating apparatus that includes an applicator, a conveyor for transporting a roll of tape to the applicator, and a metering bar positioned against the applicator to meter a predetermined amount of coating composition to the applicator, the method including applying a liquid coating composition to the applicator, and transferring the coating composition from the applicator to the edge face of the roll of tape. In one embodiment, the composition has a viscosity of at least about 15 cps. In other embodiments, the composition has a viscosity of at least about 19 cps.

In some embodiments, the end of the metering bar positioned against the applicator has a radius of at least about 3 mm. In other embodiments, the end of the metering bar positioned against the applicator has a radius of at least about 4 mm. In one embodiment, the metering bar exerts a force of at least about 35 g/cm width against the applicator. In other embodiments, the metering bar exerts a force of from about 45 g/cm width to about 900 g/cm width against the applicator.

In another embodiment, the conveyor is positioned relative to the applicator such that the applicator is capable of coating the edge face of a roll of tape disposed between the conveyor and the applicator. In one embodiment, the method further includes a second applicator positioned to receive an article from the conveyor, and a second metering bar

positioned against the second applicator to meter a predetermined amount of coating composition to the second applicator.

5 In some embodiments, the method further includes a second applicator positioned opposite the first applicator, and a second metering bar positioned against the second applicator to meter a predetermined amount of coating composition to the second applicator.

In one embodiment, the method further includes curing the composition coated on the edge face. In other embodiments, the method further includes drying the composition coated on the edge face.

10 In some embodiments, the method further includes substantially simultaneously transferring a coating composition to a first side of an article and a second side of the article opposite the first side of the article. In one embodiment, the article is a roll of tape and the method further includes substantially simultaneously transferring a coating composition to a first edge face of the roll of tape and a second edge face of the roll of
15 tape.

In other aspects, the invention features an apparatus for coating an article, where the apparatus includes an applicator roller, a conveyor for sequentially transporting a plurality of articles to the roller and a metering bar positioned against the roller to meter a predetermined amount of coating composition to the roller for transfer to an article
20 positioned between the roller and the conveyor.

The coating apparatus is capable of applying a reproducible coating weight to the surface of a series of articles upon each revolution of the applicator roller. The coating apparatus is well suited to coating the edge face of a roll of tape. The coating apparatus can coat articles that are spaced at irregular intervals on the conveyor that feeds the articles
25 into the apparatus, i.e., the interval between articles to be coated can be varied. The apparatus is also well suited to applying a coating to a number of articles each having a surface to be coated that differs in dimension from the previous article.

The coating apparatus is constructed such that when an article is not available for coating, the liquid coating composition is not transferred from the roller. The coating
30 apparatus is also capable of controlling the amount of coating composition applied to the roller such that overcoating, i.e., applying coating composition to surfaces other than the

target surface, does not occur. In the case of rolls of tape, for example, the coating apparatus is capable of coating surface variations present at the edge face of the roll of tape, while avoiding coating the vertical surfaces of the roll of tape such as the cylindrical core of the roll and the exposed backing of the roll.

5 Other features and advantages will be apparent from the following description of the preferred embodiments thereof, and from the claims. In the figures, like numbers are used to represent like elements.

Brief Description of the Drawings

Fig. 1 is a side view of a coating apparatus.

10 Fig. 2 is a side view of the metering bar of the coating apparatus of Fig. 1.

Fig. 3 is a perspective view of the metering bar of Fig. 2.

Fig. 4 is a perspective view of a roll of tape.

Fig. 5 is a side view of a coating apparatus according to a second embodiment.

Fig. 6 is a top view of the coating apparatus of Fig. 5.

15 Fig. 7 is a side view of a coating apparatus according to a third embodiment.

Fig. 8 is a front perspective view of the metering bar and applicator roller of the coating apparatus of Fig. 7.

Fig. 9 is a front view of the metering bar of Fig. 8.

Fig. 10 is a side view of a second embodiment of a metering bar.

20 Fig. 11 is a perspective view of a third embodiment of a metering bar.

Fig. 12 is a side view of a coating apparatus that includes an endless belt.

Detailed Description

The coating apparatus is suitable for coating a variety of articles including articles having a variety of different shapes and sizes. For ease of description, however, the coating apparatus is described herein with respect to coating the edge face of a roll of tape.

25 Figs. 1-4 illustrate a coating apparatus 10 for applying a liquid coating composition 24 on an edge face 16 of a roll of tape 14. The coating apparatus 10 includes an applicator 18 in the form of a roller, a metering bar 22 in contact with the applicator roller 18 and a conveyor 26. The metering bar 22 is positioned such that an edge 33 of the metering bar 26 bears on the surface of the applicator roller 18. The metering bar 22 and applicator roller 18 combine to define a trough 42, which receives the liquid coating composition 24.

The force with which the metering bar presses against the applicator roller 18 and the angle at which the arcuate end portion 31 of the metering bar 22 contacts the applicator roller 18 control the amount of coating composition 24 that is carried by the applicator roller 18 as it rotates past the metering bar 22 in a counter clock wise direction.

5 The conveyor 26 is positioned beneath the applicator roller 18 at a vertical distance from the applicator roller 18 sufficient to permit a roll of tape 14 positioned with an edge face 16 in contact with the conveyor 26 to pass between the applicator roller 18 and the conveyor 26. As the conveyor 26 moves, it transports a roll of tape 14 to the applicator roller 18. As the leading edge of the roll of tape 14 enters the coating station 54, the
10 applicator roller 18 contacts the edge face 16 and transfers a layer 12 of coating composition 24 to the edge face 16. The rotation of the applicator roller 18 in a counter clockwise direction provides fresh coating composition 24 to the edge face 16 as it travels through the coating station 54.

 The liquid composition 24 is applied to the edge face 16 at a predetermined coating
15 weight to provide a coating thickness "X" on the roll of tape. Suitable coating weights will vary depending upon factors related to the roll of tape including, e.g., the composition of the adhesive, the coating weight of the adhesive and the backing of the roll of tape and the surface variations on the edge face of the roll of tape. The apparatus 10 is capable of applying the liquid composition 24 to the edge face 16 without applying the composition
20 to the interior of the central cylinder 32 or the major surface of the exposed backing 30 of the roll of tape 14.

 Suitable applicator roller materials are conformable to the surface of the article being coated. The roller can include a single material extending through the body of the roller or multiple layers of material. Preferably the exposed roller material is sufficiently
25 conformable to apply a substantially uniform layer of coating composition on a surface having height variations. The roller can also be constructed to include one material or a number of layers of the same or different material. Roller constructions that include multiple layers preferably have a conformable outer surface layer. The applicator roller can be made from a variety of materials including, e.g., nitrile rubber, vinyl modified
30 nitrile rubbers, and urethane. The density of the applicator roller can also vary from a solid to a porous foam construction having open cell pores, closed cell pores, or a

combination thereof. Useful rollers have a hardness of from about 12 Shore A to about 55 Shore A, preferably about 24 Shore A.

Alternately, the applicator can be an endless belt. Fig. 12 illustrates a coating apparatus 110 that includes an endless belt 118 that travels around two rotating pulleys 120, 124. A metering bar 122 applies a pressure against the endless belt 118. A coating composition 24 is fed to the nip between the metering bar 122 and the endless belt 118. As the endless belt 118 moves it transports coating composition 24 and applies coating composition 24 to an edge face 116 of a roll of tape 114, which is brought into position under the endless belt 118 by conveyor 126.

The metering bar 22 is a bar that is capable of controlling the amount of coating composition applied to the applicator roller 18 such that each revolution of the applicator roller carries substantially the same amount of coating composition for transfer to the article to be coated. A number of suitable metering bar constructions are available including, e.g., a doctor blade, a doctor blade that includes a gap (e.g., an adjustable gap) as shown, e.g., in Fig. 8, and a doctor blade that includes a rotatable rod as shown, e.g., in Fig. 11. The portion of the metering bar positioned against the applicator can have a smooth or patterned surface.

The metering bar 22 of Figs. 1-3 is in the form of a doctor blade having an arcuate end portion 31. The arcuate end portion 31 is positioned and exerts a force against the applicator roller 18 during the coating process. The arcuate end portion 31 is defined by a radius "R." The radius "R" of the doctor blade 22 can be used to alter the coating weight applied to the edge face 16 of the roll of tape 14. Increasing the radius of the arcuate end portion 31 of the doctor blade 22 can cause an increase in the hydraulic force at the nip between the doctor blade 22 and the applicator roller 18, which causes an increase in the coating weight applied to the edge face 16 of the roll of tape 14. Decreasing the radius R of the arcuate end portion 31 of the doctor blade 22 can decrease the coating weight applied to the edge face 16 of the roll of tape 14. Preferably the doctor blade has a radius of at least 2.5 mm, more preferably at least about 3 mm, most preferably from about 2.5 mm to about 80 mm.

The force exerted by the metering bar 22 against the applicator roller 18 can also alter the coating weight of the composition applied to the surface of the edge face.

Increasing the force, for example, decreases the coating weight and decreasing the force increases the coating weight. Preferably the force exerted by the metering bar is from 0.25 lb/inch width to about 5.0 lb/inch width of the metering bar.

5 The coating apparatus can be used to transfer coating compositions having a wide range of viscosities including compositions having a viscosity of from about 15 centipoise (cps) to greater than 10,000 cps.

The coating apparatus can be constructed such that the applicator roller rotates continuously. The applicator roller can be connected to a motor capable of controlling the rotation as well as the rotation speed of the roller. When a roll of tape is not present in the
10 coating position, the applicator roller can continue rotating without depositing the coating composition.

Figs. 5 and 6 illustrate a second embodiment of a coating apparatus 40, which is part of a coating process that includes a coating station 54 and a finishing station 38. The coating apparatus 40 includes a second roller 52 positioned opposite the first roller 18 to
15 enable simultaneous coating of the first and second edge faces 16, 56 of the roll of tape 14. The second roller 52 is also conformable to the surface variations present on edge face 56 and includes a conformable outer layer 60. As roller 52 rotates clockwise about its axis a metering bar 22a meters a predetermined amount of liquid composition 24 to the second roller 52.

20 A conveyor 46 feeds a roll of tape 14 into the space between the rollers 18, 52. The movement of the first roller 18 in a counter clockwise direction and the second roller 52 in a clockwise direction causes the roll of tape 14 to be taken up by and passed between the two rollers 18, 52. The rollers 18, 52 then transfer a layer 12 of liquid coating composition 24 to the opposite edge faces 16, 56 of the roll of tape 14 while
25 simultaneously advancing the roll of tape 14 to the transport conveyors 34, 36.

The roll of tape 14 leaves the coating apparatus 40 via transport conveyors 34, 36, which include two endless belts 62, 64 traveling around rotating pulleys 70. The transport conveyors 34, 36 grip the roll of tape 14 as it exits from between the rollers 18, 52. The transport conveyors 34, 36 maintain the roll of tape 14 between them by friction. The roll
30 of tape 14 is preferably maintained in a level position as it is transported from the coating station 54, past the blocking panel 66 and to a finishing station 38 by the transport

conveyors 34, 36. The blocking panel 66 can block radiation, e.g., light or heat, transmitted from the finishing station 38 from reaching the coating station 54. As the roll of tape 14 passes through the finishing station 38 the layers 12 of coating composition 24 on the edge faces 16, 56 of the roll of tape 14 are treated, e.g., exposed to radiation 68 for a period sufficient to cure the layers 12 of coating composition 24 in the case of a curable coating composition or dried (e.g., by heat or air) in the case of a water-based or solvent-based coating composition. The roll of tape 14 is then transported out of the finishing station 38 to conveyor 48 for further processing including, e.g., packaging.

The coating apparatus is suitable for coating a variety of compositions including, e.g., solid (e.g., hot melt and radiation curable compositions), aqueous-based and solvent-based compositions. The coating apparatus can coat compositions having a wide range of viscosities and is well suited to coating compositions having a viscosity from about 15 cps to about 15,000 cps, preferably no greater than about 10,000 cps, most preferably no greater than about 5,000 cps.

The coating apparatus is also suitable for coating a variety of articles having varying shapes and dimensions including, e.g., piece parts.

Other embodiments are within the claims. Figs. 7-9, for example, illustrate a coating apparatus 72 that includes a metering bar 74 in the form of a doctor blade 74 that includes a gap 76 in contact with applicator roller 78. The gap 76 meters the amount of coating composition 24 that is applied to the applicator roller 78. A gap doctor blade 74 is capable of applying a greater volume of coating composition to the applicator roller 18 relative to a doctor blade without a gap. A gap doctor blade is particularly useful for coating aqueous-based compositions.

Fig. 10 illustrates a metering bar 80 that includes an arcuate portion 82 defined by radius "R1" and having a straight edge. In use, the arcuate portion 82 of the metering bar 80 is in contact with the applicator roller 18.

Fig. 11 illustrates a metering bar 86 that includes a rotatable rod 88 disposed in the applicator-contacting end 90 of the metering bar 86. The rod 88 is capable of rotating about its longitudinal axis L. The rod 88 can be rotated at predetermined speeds, at predetermined intervals and in predetermined directions, to provide various functions including, e.g., refreshing the arcuate surface available for contact with the applicator, and

cleansing the nip between the rod and the applicator. Cleansing the nip and refreshing the arcuate surface can help remove tracks and streaks formed on the applicator roller. The rotatable rod 88 is preferably a hard, dense material including, e.g., metal (e.g., steel, iron or aluminum and alloys thereof) and plastic.

5 What is claimed is:

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222